



MasterFormat: 07 17 16

JANUARY 2026
 (Supersedes September 2025)

CLAY-TITE™

Waterproofing Membrane

DESCRIPTION

CLAY-TITE is a dual layer waterproofing consisting of virgin HDPE (20 mil), sodium bentonite, and a protective layer consisting of a non-woven polypropylene. The HDPE provides the first layer of waterproofing, while the bentonite's self-sealing capabilities ensure positive puncture protection under hydrostatic conditions. The polypropylene fabric protects the bentonite from direct installation of shotcrete.

USES

Designed for use below-grade, CLAY-TITE is equally effective in installations where the waterproofing is pre-applied prior to pouring of the concrete or when used for standard applications. CLAY-TITE can be used in both vertical and horizontal applications.

FEATURES/BENEFITS

- Provides a tough, durable waterproof seal.
- Self-seals under hydrostatic conditions.
- Outstanding performance when used in high water head conditions.
- Can be installed on green or damp surfaces.

PACKAGING

3.5' x 21.5' (1.1 m x 6.6 m) or 75 SF (7 m²) standard rolls

STORAGE AND HANDLING

Protect from moisture. Store on skid or pallet; cover with polyethylene or tarp.

APPLICATION

Surface Preparation ... Surface must be smooth, sound, and void-free prior to installation of CLAY-TITE. All openings >1" (25.4 mm) must be detailed using plywood, grout, or alternate method to provide a sound substrate. Remove all sharp protrusion greater than 1/4" (6.4 mm).

For areas in which the ground water has a high sodium level (sea water or brackish water), contact W. R. MEADOWS technical services for recommendations. CLAY-TITE HSR from W. R. MEADOWS may be required in this installation. A water test may be needed to determine the suitability of the membrane for use in specific ground conditions.

Detailing ... W. R. MEADOWS offers CLAY-TITE MASTIC and CLAY-TITE ADHESIVE for seam laps. CLAY-TITE MASTIC is to be used in situations below the water table or when temperatures are going to be below 40° F (4° C). CLAY-TITE ADHESIVE is to be used when above the water table and temperatures are above 40° F (4° C). In most applications, CLAY-TITE MASTIC is the preferred product.

Blindside Installation ... Ensure that surface to be waterproofed is sound and void-free. The use of MEL-DRAIN 5035 from W. R. MEADOWS is recommended for all applications. Mechanically attach MEL-DRAIN to soil retention. CLAY-TITE can be installed either vertically or horizontally with the HDPE surface towards the drainage board. Mechanically affix CLAY-TITE across the top every 20" (508 mm). Lap all seams a minimum of 4" (101.6 mm). If installed in the horizontal direction, ensure that seams are shingled in a manner to shed water. All seams should be nailed every 2' (0.6 m) and a staple placed between the nails. Apply CLAY-TITE MASTIC from W. R. MEADOWS over all fasteners. For detailed instructions, refer to CLAY-TITE BLINDSIDE INSTALLATION GUIDELINE available at www.wrmeadows.com.

Backfilled Wall ... Install CLAY-TITE with the bentonite side towards the concrete. At the top of the membrane, affix TERMINATION BAR from W. R. MEADOWS. All lap seams must overlap at least 1.5" (38 mm). Make sure to shingle all overlaps to shed water. Mechanically attach all seams at 24" (609.6 mm) on center and apply PMPC TAPE from W. R. MEADOWS on joint. For detailed instructions, refer to CLAY-TITE BACKFILLED WALL INSTALLATION GUIDELINES available at www.wrmeadows.com.

CONTINUED ON REVERSE SIDE ...

W. R. MEADOWS, INC.

P.O. Box 338 • Hampshire, IL 60140-0338
 Phone: 847/214-2100 • Fax: 847/683-4544
 1-800-342-5976
www.wrmeadows.com • info@wrmeadows.com

HAMPSHIRE, IL / CARTERSVILLE, GA / YORK, PA
 FORT WORTH, TX / BENICIA, CA / POMONA, CA
 GOODYEAR, AZ / MILTON, ON / SHERWOOD PARK, AB

Underslab ... CLAY-TITE is designed to act both as a waterproofing and vapor barrier membrane when installed underslab. Place membrane bentonite side up on the mud slab or over compacted sub-grade. Overlap and stagger seams at least 4" (101.6 mm). Protect from flooding prior to pouring of concrete. Refer to ACI 302.1R-04: Chapter 4 – Site Preparation and Placing Environment for sub-grade preparation. For detailed instructions, refer to CLAY-TITE UNDERSLAB INSTALLATION GUIDELINES available at www.wrmeadows.com.

Penetrations and Protrusions ... Fill void around penetration with CLAY-TITE GRANULAR PACK from W. R. MEADOWS or CLAY-TITE MASTIC. Trowel CLAY-TITE MASTIC covering the penetration. Using a 6" (152.4 mm) cut strip of CLAY-TITE, form a collar around the penetration and hold in place with fasteners. Install WATERSTOP EC from W. R. MEADOWS around the penetration.

LIMITATIONS/PRECAUTIONS

CLAY-TITE installation must be confined by a minimum of 24 lb./ft.² (117.2 kg/m²). Keep CLAY-TITE dry; protect from exposure to the elements. Do not install in areas of ponding water or ice. For installation temperatures below 40° F (4° C), use CLAY-TITE MASTIC in place of CLAY-TITE ADHESIVE. In areas under constant hydrostatic head conditions, all joints and seams are to be detailed using CLAY-TITE MASTIC.

For most current data sheet, sustainability information, and SDS, visit www.wrmeadows.com.

TECHNICAL DATA

Property	Test Method	CLAY-TITE Results
Membrane		White 20-mil Virgin Resin HDPE
Bentonite		Sodium Montmorillonite
Total Thickness		150 Mils
Weight		1 lb./ft. ² (4.89 kg/m ²)
Puncture Resistance	ASTM E154, Section 10	170 lb. (77.1 kg)
Tensile Strength, Membrane	ASTM D638	MD: 3660 psi (25.2 MPa) TD: 3650 psi (25.2 MPa)
% Elongation at Break	ASTM D638, Type I dogbone	>700%
Crack Bridging		3/8" (9.6 mm) Crack
Hydrostatic Pressure Resistance	ASTM D5385	231' (70.4 m) of water 100 psi (690 kPa)
Water Vapor Permeability	ASTM E96-80	0.53 x 10 ⁻¹³ cm/sec 0.84 ng/ m ² .s.Pa 0.033 Perms (grains/ft. ² * hr * inHg)
Freeze/Thaw Cycles		No effect before or after installation.
Installation Temperatures		-40° to 150° F (-40° to 65.5° C)



LIMITED WARRANTY

W. R. MEADOWS, INC. warrants at the time and place we make shipment, our material will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. Read complete warranty. Copy furnished upon request.

Disclaimer

The information contained herein is included for illustrative purposes only, and to the best of our knowledge, is accurate and reliable. W. R. MEADOWS, INC. cannot however under any circumstances make any guarantee of results or assume any obligation or liability in connection with the use of this information. As W. R. MEADOWS, INC. has no control

over the use to which others may put its product, it is recommended that the products be tested to determine if suitable for specific application and/or our information is valid in a particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each product. Specifier and user shall determine the suitability of products for specific application and assume all responsibilities in connection therewith.